



OM 22

Industrial benchtop micro-ohmmeter
- High accuracy: 0.03 %

REPLACE PAR LE NOUVEAU [OM37](#) (disponibilité été 2025)

Le micro-ohmmètre industriel de table OM 22 est destiné à la mesure en 4 fils de résistances de très faibles valeurs jusqu'à 20 K Ω avec une excellente précision maximale de 0,03% et une résolution de 0,1 $\mu\Omega$ seulement. Doté de 6 programmes, il est particulièrement adapté à un usage sur banc pour l'exécution de tâches de mesures répétitives. La fiabilité et la précision des mesures est renforcée par le faible coefficient de température (10 ppm/°C), la compensation automatique des forces électromagnétiques avant chaque mesure effectuée, la compensation en température de la nature du métal et la compensation de la température ambiante.

Description

OM 22 benchtop micro-ohmmeter is used for 4-wire measurement of very low resistance values up to 20 K Ω with an accuracy of 0.03% RDG and a 0.1 $\mu\Omega$ resolution. Programmable, it is particularly suited for use on test benches with repetitive measurement tasks. The reliability and accuracy of the measurements is improved by a low temperature coefficient of 10 ppm/°C, automatic removal of EMF parasites before each measurement, metal temperature compensation and compensation of ambient temperature.

With three current waveforms available -continuous, pulse or AC current- from 100 μA to 10 A and high flexibility of trigger and sampling conditions, OM 22 low resistance ohmmeter covers a wide range of applications: Cable resistance and resistivity measurement, inductive resistance measurement (motors and transformers winding resistance), contact resistance measurement (connectors, switches, relays...), test of low power electrical components (fuses...) and heat sensitive devices, metallisation / earth bonding and ground continuity measurement.

OM 22 is a programmable instrument, ideal for use on test benches: it has 6 configurations to be modified and recalled by users upon request through the 6 direct keys on the front board. Every configuration defines every measurement aspects: range, current waveform and value, number of measurements per cycle with temporisation, storage conditions, temperature compensation, measuring unit, metal under test, calculations of coil heating or W/km, alarm settings, maximum measurement voltage, analogue output, trigger conditions...

If necessary, OM 22 configurations can be modified through LOG OM data management software delivered in the standard package.

Up to 1,000 samples can be stored inside the instrument and be recalled directly on the display or on computer via LOG OM.

Powered from mains or from rechargeable batteries in option, the electronic calibration of the instrument is performed without any internal adjustment.

Specifications

Resistance measurement

Range	Resolution	Accuracy at 90 days (23°C ±1°C)	Measuring current	Voltage drop
2 mΩ	0.1 μΩ	0.05% + 0.3 μΩ	10 A	20 mV
20 mΩ	1 μΩ	0.05% + 2 μΩ	10 A	200 mV
20 mΩ	1 μΩ	0.05% + 3 μΩ	1 A	20 mV
200 mΩ	10 μΩ	0.05% + 10 μΩ	10 A	2 V
200 mΩ	10 μΩ	0.05% + 20 μΩ	1 A	200 mV
200 mΩ	10 μΩ	0.05% + 30 μΩ	100 mA	20 mV
2 Ω	100 μΩ	0.05% + 100 μΩ	1 A	2 V
2 Ω	100 μΩ	0.03% + 200 μΩ	100 mA	200 mV
2 Ω	100 μΩ	0.03% + 300 μΩ	10 mA	20 mV
20 Ω	1 mΩ	0.03% + 1 mΩ	100 mA	2 V
20 Ω	1 mΩ	0.03% + 2 mΩ	10 mA	200 mV
20 Ω	1 mΩ	0.03% + 3 mΩ	1 mA	20 mV
200 Ω	10 mΩ	0.03% + 10 mΩ	10 mA	2 V
200 Ω	10 mΩ	0.03% + 20 mΩ	1 mA	200 mV
200 Ω	10 mΩ	0.03% + 30 mΩ	100 μA	20 mV
2 kΩ	100 mΩ	0.03% + 100 mΩ	1 mA	2 V
2 kΩ	100 mΩ	0.03% + 200 mΩ	100 μA	200 mV
20 kΩ	1 Ω	0.03% + 1 Ω	100 μA	2 V

Automatic or manual selection of measurement range
Accuracy given in % of reading + counts over 90 days at 23 ±1°C
Maximum capacity: 26,000 counts

Further features

Configurations	6 configurations available, to be modified if necessary with LOG OM software delivered in standard
Resistance types	<ul style="list-style-type: none"> • Inductive resistances: Coils, transformers, motor windings... • Non-inductive resistances: Earth bonding, coating, contact resistances...

Measuring current	<ul style="list-style-type: none"> • Internal or external source • DC current from 100 μA to 10 A • Continuous, pulsed or pulsed alternated
Measurement time	<p>< 1 s in direct current mode < 1,5 s in pulse current mode < 2 s in alternate current mode</p>
Measurement trigger conditions	Manual or automatic trigger from 2 measures/s to 1 measure/9h, allowing a single operator to be able to perform measurements
EMFs	Automatic compensation of EMF parasites before each measurement for a greater accuracy
Temperature compensation	<p>Choice of metal temperature coefficient Choice of ambient temperature (programmed or measured with external probe) Temperature compensation at 20°C: Resolution: 0.1°C, accuracy: $\pm 0.5^\circ\text{C}$ (R20 = Resistance compensated at ambient temperature equal to 20°C)</p>
Temperature coefficient beyond operating range	< 10% accuracy/ $^\circ\text{C}$
Relative measurements	<p>Display $L = R - R_0$ or $L = 100 \times (R - R_0) / R_0$ in % Where L: read value, R: measured value and R₀: reference value either recalled from memory or entered by the operator</p>
Coil heating calculation	Coil heating calculation according to ambient temperature, original coil resistance at ambient temperature, coil resistance once heated and coil material
Alarms	2 programmable thresholds with visual and sound signal and relay outputs
Outputs	<ul style="list-style-type: none"> • Two relays (1 A / 220 VAC) • 1 analogue output 0 - 2.5 V (load \geq 2.5 kΩ, resolution: 10 mV, accuracy: ± 10 mV)
Calibration	Digital calibration without internal adjustment

General specifications

Size	225 x 88 x 310 mm
Weight	2 to 3 kg depending on options
Display	LCD 26,000 counts, 16 figures lighted, 11.5 mm high
Power supply	115 / 230 V (50 / 60 Hz)
Battery with internal charger(option)	<p>Type: 12 V battery pack Battery life: 2 to 8 h according to use</p>

Charging time: 14 h

Storage capacity	1,000 measurements with average, minimum and maximum value Memory reading directly on the display or through digital and analogue interfaces
------------------	---

Environmental specifications

Reference range	23°C ±1°C (RH: 45 to 75% w/o condensing)
Operating reference range	0 to 50°C (RH: 20 to 80% w/o condensing)
Limit operating range	-10°C to +50°C (RH: 10 to 80% w/o condensing)
Storage temperature limits	-30°C to +55°C (-15°C to +50°C for model with battery)
Protection IP	IP40 according to EN60529
Maximum altitude	2,500 m

Safety specifications

Protections

- Electronic protection for 'voltage' wires
- Fuse protection for 'current' wires
- Protection against 'current' circuit breaking during inductive resistance measurements

Class

In accordance with EN 61010-1
Category III, pollution 2

Rated voltage

50 V

Chocks and vibrations

EN61010-1

EMC conformity

Models and accessories

Instrument:

OM 22-1	Industrial benchtop micro-ohmmeter With RS 232 interface
OM 22-2	Industrial benchtop micro-ohmmeter With RS 232 interface and battery + charger
OM 22-3	Industrial benchtop micro-ohmmeter With RS 232 interface and IEEE 488
OM 22-4	Industrial benchtop micro-ohmmeter With RS 232 interface, IEEE 488 and battery + charger

Delivered in standard with LOG OM configuration software

Clips and probes:

Please note that 2 clips are needed per OM 22.

AN5806-2	Gold plated Kelvin clips, set of 2 Opening diameter: 12 mm, cable length: 2 m
AN5806C	Kelvin clips, set of 2 Opening diameter: 12 mm, cable length: 3 m
AMT003	Test probe, per unit Cable length: 5 m
AMT004	Kelvin clip, per unit Opening diameter: 25 mm, cable length: 3 m

Other accessories:

LOG OM	Configuration & exploitation software for OM 22 Including RS 232 cable
AN6901	Soft case for benchtop instruments
AMT002	External power supply 3 V – 10 A
AN5883	Bracket mounting for panel installation (T2 box type)
AN5884	Rack mounting kit for rack installation (T2 box type)
AN5875	RS232 9p F cable
AN5836	IEEE 488 cable



Length: 2 m

AN8009

Set of 10 fuses - 16 A

Certification:

QMA11EN

COFRAC certificate of calibration