



UNIGAS 1000

Hand-held basic combustion gas analyzer with 2 sensors



UniGas 1000+ is a basic flue gas analyzer for 2 gases: O_2 & CO with electrochemical sensors, plus CO_2 calculated.

Description

UniGas 1000+ is a basic flue gas analyzer for 2 gases: O_2 & CO with electrochemical sensors, plus CO_2 calculated.

The instrument is delivered with a built-in rugged impact printer. The analyzer and its internal printer are powered by the same internal battery. Charger is supplied as standard.

Smoke index measurement is performed by using the optional external hand pump (ref: F7828000). The results can be stored in the internal memory and printed on the report.

A procedure can be selected to monitor the CO in ambient air using the internal sensors. An internal program allows CO max measurement in atmospheric boiler room test with 15 logged values.



Specifications

Measured parameter	Range	Resolution	UniGas 1000
02	From 0 to 25% vol.	0.1%	EC
CO	From 0 to 8000 ppm	1 ppm	EC
CO2	From 0 to 99.9%	0.1%	Calc
Efficiency	From 1 to 99.9%	0.1%	Calc
Excess air	From 1 to infinite	0.01%	Calc
Pressure / Draft	From -10 to 120 hPa	0.01 hPa	1
Tair/Tgas	-10100°C/ 0600°C	0.1°C	Pt100 / Tc K Calc

Further features

Zero calibration	Automatic calibration procedure at instrument power-on. Fresh air inlet with electrovalve and separate pneumatic circuit
Self-diagnosis	Sensor efficiency test with diagnostic page
Sampling pump	1.4 l/min - 100 mbar
Smoke measurement	Using the external manual pump
Printer	24 columns with 58 mm paper roll Autonomy: 40 reports with full battery

General specifications

Size	115 x 90 x 330 mm
Weight	1.1 kg with battery and printer
Power supply	110 / 230 VAC (50/60 Hz)
Battery	Type: Rechargeable Li-ION Battery life: 6 hours continuous use Charging time: 8 h at 90%
Communication ports	RS 232

Environmental specifications

Operating reference range	From -5°C to +45°C (up to 50°C for short time)
Storage temperature limits	From -20 to +50°C (3 months max. at temperatures exceeding the operational limits)



Models and accessories

Instrument:

Ordering code structure: 7820 - A - B - C - D - E - F / X

Please select the required options from tables A, B... below to define the right device reference.

7820 UniGas 1000

Standard delivery includes:

- Base unit with 2 sensors (O₂ + CO)
- Li-ION battery + charger module
- Internal impact printer
- IR port for thermal printer
- Factory test report
- Instruction manual
- Warranty: 1 year

Table A - Sensor n°1(1 choice only)

1 $O_2 (0 - 25\%)$

Table B - Sensor n°2 (1 choice only)

2H CO (0 - 8,000 ppm) H_2 compensated + Dilution system

Table C - Sample probes - including water trap and line filter (1 choice only)

0 None

1 180 mm sampling dual hose probe BB610051 (Gas + Draft) - max 800°C

2 300 mm sampling dual hose probe BB610046 (Gas + Draft) - max 800°C

Table D - Options (P is mandatory)

P Built-in impact printer

Table E - Mains adapter / Charger (1 choice only)

- 1 115 V 50 / 60 Hz USA plug
- 3 230 V 50 / 60 Hz UK plug
- 4 230 V 50 / 60 Hz European plug
- 5 100 V 50 / 60 Hz USA / Japan plug



Table F - Calibration certificate

1 Factory certificate (gas + pressure + temperature)

Table X - Customization

INTL English language - manual in English - English Keyboard
USA English language - manual in English - English Keyboard
FR French language - manual in French - French Keyboard
HOL Dutch language - manual in English - English Keyboard
POL Polish language - manual in English - English Keyboard
SPA Spanish language - manual in English - English Keyboard
UK English language - manual in English - English Keyboard

Accessories:

Probes and sensors:

BB610051 180 mm sampling dual hose probe BB610051 (Gas + Draft) - max 800°C

BB610046 300 mm sampling dual hose probe BB610046 (Gas + Draft) - max 800°C

BB830018 Pt100 remote air temperature sensor, with 2 m cable and positioning cone

F2132100 130 mm air TC K-type probe

F2137100 130 mm contact TC K-type probe

F2139000 Pipe Velcro TC K-type probe

Test tools and miscellaneous:

EE300088 Single hose pressure probe and burner hose kit

F7828000 Manual pump for smoke index measurements + 40 filters + table

Software and connectors:

BB260166 DBGas 2004 standard software

EE700476 USB adaptator cable

Transport cases and protections:

BB880028 ABS rigid carrying case

BB880043 Vinyl carrying case with shoulder strap

EE880047 Rubber holster with magnetic support



Consumable parts:

EE340006 Printer paper roll - Minimum order of 10 pcs

EE490002 Printer ribbon - Minimum order of 3 pcs

EE650011 Filter for soot (40 pieces per pack)

EE650074 Filter cartridge for EE650076 / EE 650082 water trap + filter - *Minimum order of*

10 pcs