



## CTI45

CTI45 Ohmmeter, Insulation  
Megohmmeter, microhmmeter

Safety pyrotechnic ohmmeter, Insulation Megohmmeter

## Description

The CTI45 is an Ohmmeter, megohmmeter, microhmmeter designed for pyrotechnics safety. It was developed for measurements in industrial environments, controls on production lines and in laboratory. It is designed for measurements on pyrotechnic elements considering user safety. Its main strengths lie in its great versatility and high speed measurement.

Measurement conditions and safety

- Measuring current much lower than the non-fire current
- Connection to the test line only during the measurement period
- Not exceeding a maximum current of safety during a failure of the equipment (electronic failure, internal short circuit, ...)
- Discharge of residual electrostatic charge
- Permanent self-monitoring equipment's internal functions
- External Safety loop enable power measurement circuitry

### Functions

- Ohmmeter / microhmmeter: CTI45 has 4 main measurement channels four wire, with the ability to perform cross channel measures to adapt to more complex configuration
- Megohmmeter: It allows isolation measures, taken between 2 of the 4 main Ohmmeter channel with configurable voltage (or fixed at order).
- PT100 function: temperature measurement
- Macro: CTI45 allows groups measurement without user intervention, in the form of macro commands
- Display: Setting the LCD screen to fit your needs
- Communication: Access mode Telnet, TCP or RS232 providing convenient automated control

### Main Features

- 4/8 channels
- Ohmmeter ranges: 1 $\Omega$ /10 $\Omega$ /100 $\Omega$ /1K $\Omega$ /10K $\Omega$
- Megohmmeter range: 1M $\Omega$ /10M $\Omega$ /1G $\Omega$
- Megohmmeter test voltage: 45 to 500V, customizable or fixed value
- Bench top or rack 19" 2U P260
-

# Specifications

## Functions:

Ohmmeter:

Ranges	10 $\Omega$	100 $\Omega$	1 k $\Omega$	10 k $\Omega$
Resolution	100 $\mu\Omega$	1 m $\Omega$	10 m $\Omega$	0.1 $\Omega$
measuring current	10 mA	1.5 mA	250 $\mu\text{A}$	50 $\mu\text{A}$

Megohmmeter / insulation tester

Ranges	10 M $\Omega$	100 M $\Omega$	1G $\Omega$
Resolution	1 k $\Omega$	10 k $\Omega$	100 k $\Omega$
Measuring voltage	Max. 50 V	Max. 500 V	Max. 500 V

Low resistance measurement : micro ohmmeter:

Range	1 $\Omega$
Resolution	1 $\mu\Omega$
Measuring current	10 $\mu\text{A}$
Accuracy	0.05% + 100 $\mu\Omega$
Measuring time	From <100 ms up to ~1s according to integration time

## Other specifications

Power supply

Main specifications:

- Voltage: 85V~ to 264V~ / 45 to 63Hz
- Power: 10W
- Fuses : 2 x 400mA T

-

mechanical and environmental specifications



# Models and accessories

Rack mounted version  
IP 44 version with heavy duty connectors