



LGR30-001

Temperature Sensor

Measuring range: -250°C... +850°C

Accuracy: $\pm 0.24^\circ\text{C}$

PT100 sensor

Certification : CE

Description

The LGR30 is a temperature sensor that can be used in two different modes:

Monitoring: the logger sends its measurement to the PC in real time. If a measurement is not received by the PC, it stores it in its internal memory and sends it to the PC on the following communication channel "recording".

Playback: The recorder stores the measurements it takes in its memory. The user can download any stored measurements to the PC.

It is also equipped with :

IP65 enclosure

$\frac{1}{2}$ wave antenna

Power supply AA Lithium Thionyl battery

Specifications

| LGR30 | |
|--|--|
| Type | Pt100 Compliant with 2 wire, 3 wire and 4 wire (recommended) |
| Temperature range of use of the logger | -40°C... +85°C |
| Measurement range | -250°C ... +850°C (max. range) |
| Accuracy | ± 0.24°C (to be added to the probe accuracy) |
| Resolution | 0.08°C |

| | |
|-----------------------|---|
| Antenna RF Connector | SMA connector |
| Antenna | ½ Wave antenna (included) |
| RF range in free land | 100m to 1km, depending on the antenna used on the reception side |
| Memory Capacity | 32 256 measurements with date and time |
| Time resolution | 1s |
| Time deviation | +/- 2min/month at 25°C |
| Data memory retention | 100 years |
| ILS | ILS integrated for several functions : - Wakeup of the product in hibernate mode - Take of a measure outside of the frequency measure set |

| | |
|----------|--|
| IP | IP65, the level of tightness of the product is valid only if the probe and antenna are properly tightened (seals crushed) |
| Battery | AA lithium Thionyl (included) with plug-in connector |
| Autonomy | Up to 3 years At 25°C with a frequency measures of 10 minutes. Average value which can slightly vary depending on the use. It is given with the product working in non alert mode. |

Specifications :

| | |
|----------|---|
| Features | Aluminium casing (4mm) |
| Fixation | Fixation support provided screwed in the casing for screwing in 4 points or strapping through 2 holes |

| | | |
|------------|---|-------|
| Colour | Grey (aluminium) | |
| Dimensions | Length | 98 mm |
| | Depth | 64 mm |
| | Heigth | 34 mm |
| Weight | About 280g | |
| Stickers | <p>2 stickers on the product :</p> <ul style="list-style-type: none">- 1 sticker on the top face, giving the product range- 1 sticker on the side, giving the complete product reference and its serial number | |