



LGR37-001

Temperature Sensor



Thermocouple K

measuring range: -273...1372°C Accuracy: ±0.1°C

Certification: CE

Description

The LGR37 is a temperature sensor that can be used in two different modes:

Monitoring (real-time monitoring applications): the logger sends its measurements to the PC in real time. If a measurement is not received by the PC, it stores it in its internal memory and sends it to the PC on the "recording" communication channel.

Recording/retrieval (a posteriori control): the logger records the measurements it takes in its on-board memory. The user can download all the stored measurements to his PC whenever he wants.

It operates on thermocouples, and is also equipped with :

IP65 enclosure (aluminium)

 $\frac{1}{2}$ wave antenna

Power supply AA Lithium Thionyl battery

Translated with DeepL.com (free version)



Specifications

| LGR37 | | |
|--|------------------|--|
| Туре | For Thermocouple | |
| Temperature range of use of the logger | -40°C +85°C | |
| Measurement range | -40°C +100°C | |
| Accuracy | ± 0.3°C | |
| Resolution | 0.1°C | |

| Antenna RF Connector | SMA connector |
|-----------------------|--|
| Antenna | 1/2 Wave antenna (included) |
| RF range in free land | 100m to 1km, depending on the antenna used on the reception side |
| Memory Capacity | 32 256 measurments with date and time |
| Time resolution | 1s |
| Time deviation | +/- 2min/month at 25°C |
| Data memory retention | 100 years |
| ILS | ILS integrated for several functions : - Wakeup of the product in hibernate mode - Take of a measure outside of the frequency measure set |

| IP | IP65, the level of tightness of the product is valid only if the probe and antenna are properly tightened (seals crushed) |
|----------|--|
| Battery | AA lithium Thionyl (included) with plug-in connector |
| Autonomy | Up to 3 years At 25°C with a frequency measures of 10 minutes. Average value which can slightly vary depending on the use. It is given with the product working in non alert mode. |

Specifications :

| Features | Aluminium casing (4mm) |
|----------|---|
| Fixation | Fixation support provided screwed in the casing for screwing in 4 points or strapping through 2 holes |



| Colour | Grey (aluminium | | |
|------------|--|-------|--|
| Dimensions | Length | 98 mm | |
| | Depth | 64 mm | |
| | Heigth | 34 mm | |
| Weight | About 280g | | |
| Stickers | 2 stickers on the product : 1 sticker on the top face, giving the product range 1 sticker on the side, giving the complete product reference and its serial number | | |