



**LGR46-001**

Temperature Sensor

Measuring range: -40°C...100°C

Accuracy :  $\pm 0.3^{\circ}\text{C}$

Certification: CE

## Description

The LGR46 is a temperature sensor that can be used in two different modes:

**Monitoring** (real-time monitoring applications): the logger sends its measurements to the PC in real time. If a measurement is not received by the PC, it stores it in its internal memory and sends it to the PC on the following communication channel: "recording".

**Recording/retrieval** (a posteriori control): the logger records the measurements it takes in its on-board memory. Users can download all stored measurements to their PC at any time.

It is also equipped with :

IP65 enclosure (Aluminium)

$\frac{1}{2}$  wave antenna

Power supply AA Lithium Thionyl battery

# Specifications

| LGR46                                  |  |
|--|--|
| Type                                   | For Newsteo Double external probe of Temperature |
| Temperature range of use of the logger | -40°C... +85°C                                   |
| Measurement range                      | -40°C... +100°C                                  |
| Accuracy                               | ± 0.3°C  |
| Resolution                             | 0.1°C  |

|                       |   |
|-----------------------|---|
| Antenna RF Connector  | SMA connector   |
| Antenna               | ½ Wave antenna (included)   |
| RF range in free land | 100m to 1km, depending on the antenna used on the reception side  |
| Memory Capacity       | 32 256 measurments with date and time   |
| Time resolution       | 1s  |
| Time deviation        | +/- 2min/month at 25°C  |
| Data memory retention | 100 years   |
| ILS                   | ILS integrated for several functions :<br><ul style="list-style-type: none"> <li>- Wakeup of the product in hibernate mode</li> <li>- Take of a measure outside of the frequency measure set</li> </ul> |

|          |   |
|----------|---|
| IP       | IP65, the level of tightness of the product is valid only if the probe and antenna are properly tightened (seals crushed)   |
| Battery  | AA lithium Thionyl (included) with plug-in connector  |
| Autonomy | Up to 3 years<br>At 25°C with a frequency measures of 10 minutes. Average value which can slightly vary depending on the use. It is given with the product working in non alert mode. |

## Specifications :

|          |   |
|----------|---|
| Features | Aluminium casing (4mm)  |
| Fixation | Fixation support provided screwed in the casing for screwing in 4 points or strapping through 2 holes |

|            |  |       |
|------------|--|-------|
| Colour     | Grey (aluminium)   |       |
| Dimensions | Length   | 98 mm |
|            | Depth  | 64 mm |
|            | Height   | 34 mm |
| Weight     | About 280g   |       |
| Stickers   | 2 stickers on the product :<br>- 1 sticker on the top face, giving the product range<br>- 1 sticker on the side, giving the complete product reference and its serial number |       |